

Front

Back



Product	8 Port Fast Ethernet Switch
Fixed Port	8*10/100Base-TX RJ45 port (Data)
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x
Port Specification	10/100BaseT(X)Auto
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	1.6Gbps
Packet Forwarding	1.15Mpps
MAC Address	1K
Buffer	768K
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter)
Watt	Standby Power Consumption: ≤3W;
LED Indicator	PWR:Power LED 1-8: (Link LED=10/100M Link)
Power	External Power DC: 5V
Operating Temperature/Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	125mm*60mm*24mm 131mm*70mm*65mm
N.W/G.W (kg)	0.3kg/0.5kg
Installation	Desktop
Lightning protection level	IP30
Certificate	CE FCC RoHS
Warranty	Whole device for 3 year(Accessories not included)